



OKLAHOMA SOUND CORPORATION

**VENEER CONTEMPORARY
Lectern 900 Series**

PRODUCT HANDBOOK



MODEL # 950/901/910

SERIES 900 VENEER CONTEMPORARY LECTERN

Lecterns are constructed of plywood and hardwood for strength and rigidity. Makes a strong design statement while blending with almost any decor. Presents a stately and sophisticated appearance that works well in corporate or executive offices. Appealing curvilinear design makes it suitable for conference rooms, and training rooms.

CARE OF YOUR CABINET

All exterior and interior exposed surfaces are veneer covered as well as edges in matching patterned veneer material. To refresh the appearance, wipe the surface with a cloth soaked lightly in furniture oil. Avoid speaker grill area. Your cabinet will look as good as new.

MODEL #910 NON-SOUND TABLE LECTERN

Rich Veneer Lectern on Plywood Core in Contemporary/Transitional style commands a dignified presence. Modern stylistic radius curves and contoured edging. Concealed Florescent Reading Lamp illuminates generous reading surface large enough for 3 ring binder. Digital timepiece included. Choice of two finishes: Cherry on Cherry or Mahogany on Walnut. Reading surface 22"W x 14"L. One shelf 9"H x 11"L x 23"W. Total Height 22".

MODEL #901 LECTERN BASE

Rich Veneer Lectern Base on Plywood core in Contemporary/Transitional style Rich Veneer Lectern Top to a full floor Lectern commanding a dignified presence. Modern stylistic radius curves. Two locking doors conceal an Adjustable Shelf with five adjustment levels. Fingertip cutouts for easy door opening. Rolls easily on four furniture grade casters. Choice of three finishes: Cherry on Cherry or Mahogany on Walnut. Two shelves. Each 11"H x 16"D x 22"L. Total Height 26.5".

MODEL #950 TABLE LECTERN WITH SOUND

Rich Veneer Amplified Sound Lectern on Plywood Core in Contemporary. Transitional style commands a dignified presence. Modern stylistic radius curves and contoured edging. Custom built in 75 watt Multimedia Amplifier Sound System broadcasts for audiences up to 7500 people or 75,000 sq. ft. Four 4-inch speakers mounted directly on radius corners with radius style grille, contribute to the Luxurious appearance and afford high quality audio amplification. Multimedia capabilities include capacity for two microphones and one wireless user. Inputs for tape and CD and extension speaker and recording outputs. Concealed Florescent Reading Lamp illuminates generous reading surface large enough for 3 ring binder. Digital timepiece included. Choice of two finishes: Cherry on Cherry or Mahogany on Walnut. When placed on #901 Base, Total Height 49". One shelf each 9"H x 11"L x 23"W.

Specifications (Model #950)

- Power Output 75 Watt
- Microphones 2 condenser types:
 - Handheld with 9" cable
 - & Tie Clip with 10" cable.
- Speakers. Four 4" High Efficiency Speakers.
- Input 2 Mics, 1 Aux./Wireless
- Output Line out 1-Extension Speaker, Line out 2-Tape Recorder.
- Controls Four Volume, Bass/Treble, On/Off Fuse Internally Mounted, 2A
- Power Supply. 117 Volt AC; 12 V DC w/ Optional Battery
- Recharger Internally mounted; with LED indicator.
- Dimensions. 47"H x 22"W x 18"D.



900 SERIES AMPLIFIER OPERATING INSTRUCTIONS

Operating Precautions

Before operating the amplifier, be sure you fully understand all instructions and features of the amplifier. DO NOT turn amplifier on until all input and output connections have been made. NEVER replace fuses unless power is off.

Microphone Input Connection

The microphone input accepts 1/4" phone jack. Do not position microphone next to or facing speakers. This may cause acoustic feedback.

Auxiliary Input

One auxiliary input is provided for radio tuner, tape recorder, CD player or multi-media equipment. Output level is adjusted by the auxiliary volume control.

Tone / Equalization Controls

The Low and High frequency controls are similar to the bass and treble controls found on most stereo systems. Optimum tone is achieved by first setting both knobs halfway; adjust Low and High frequency controls to suit environment.

Auxiliary / Line Out

Connect additional speaker line to navy line out connector of the amplifier. For maximum power transfer and to avoid amplifier overload, be sure that the total impedance of the speaker line matches the output impedance setting on amplifier. *Be sure* that speaker terminals are not shorted together by speaker line connecting cables. Can also be used for a recording device.

Power Supply 12V DC Operation

Connect a 12 volt rechargeable battery 5 Amp (not included) to the battery input connector located on the panel of the amplifier (using 6' battery cable). Be sure that the positive pole of battery is connected to the white wire terminal (+) and the negative pole to the Brass wire (-). When lectern is plugged into a standard wall outlet, the battery will automatically recharge. Green indicator light illuminates during recharge mode.

Precautions

- Set Mic volume control on lowest when turning unit on.
- Insure correct polarity for D.C. supply connections.
- Reverse connection will blow the fuse and may damage internal circuitry.
- Always replace fuse with specified rating.

Removal and Installation of Amplifier

If your amplifier has to be removed for servicing — follow these simple steps:

- 1) Disconnect A/C wall plug.
- 2) Remove 4 side screws two on each side panel under amp top.
- 3) Disconnect speaker wire at rear of amplifier.
- 4) Pack it into a strong box with ample cushioning and return to factory.
- 5) To install new amplifier reverse the above procedure.

OPTIONAL/ADDITIONAL EQUIPMENT

Your lectern includes two corded microphones.
For complete freedom of movement, use any of these wireless systems—

USE WITH WIRELESS AMPLIFIERS



HAND-HELD WIRELESS MIC. / LWM-5
This wireless hand-held Mic. Uses a 9-volt battery. Select channel A or B to eliminate outside frequency interruption. Move freely up to 200 ft. away!



TIE-CLIP LAVALIER WIRELESS MIC. / LWM-6
Includes pocket-size transmitter with a clip-on mic. Uses a 9-volt battery. Select channel A or B to eliminate outside frequency interruption. Move freely up to 200 ft. away!



HEADSET WIRELESS MIC. / LWM-7
Includes pocket-size transmitter with a headset mic. Uses a 9 volt battery. Select channel A or B to eliminate outside frequency interruption. Move freely up to 200 ft. away!

USE WITH NON-WIRELESS AMP or added wireless users



TIE CLIP LAVALIER WIRELESS MIC SYSTEM / #WM-190TC
A compact, pocket-size, wireless system with tie-clip, lavalier type microphone. Includes transmitter, receiver and tie clip mic. Move freely up to 200 ft. Operates on two 9V batteries.



12V LANTERN STYLE RECHARGEABLE BATTERY / #PS12V
12V 5 amp rechargeable battery pack w/included cable connects to any of our lecterns for battery power. 20 hr life.



WIRED-WIRELESS MIC SYSTEM / #WM-100H
Hand-held wireless mic system. Receiver has antenna and on/off switch. Transmitter is built into mic. Move freely up to 50 ft. Mic uses AA battery; receiver uses AAA battery.

For these products please contact your dealer or Oklahoma Sound Corp.

Manufacturers Warranty

Our Lecterns undergo the most rigid and exacting tests for superior quality and performance before leaving the factory. Oklahoma Sound Corporation warrants this product to be free from defective material and workmanship on the electronic product speakers and microphones for two years from the date of resale by an authorized Oklahoma Sound distributor. Oklahoma Sound will replace defective parts and repair malfunctioning products under this warranty when the defect occurs under normal installation and use, provided the unit is returned to our factory via prepaid transportation after direct authorization and approval by Oklahoma Sound. This warranty provides that examination of the returned product must disclose in our judgement, a manufacturing defect. This warranty does not extend to any product which has been subject to misuse, neglect, accident, improper installation, or where the serial number has been removed or defected and is given in lieu of any other warranty implied or expressed and will not cover any consequential damages.

OKLAHOMA SOUND CORP.

149 Entin Road, Clifton, NJ 07014 Tel: 973-594-9000 • Fax: 973-594-9339
Web-Site <http://www.oklahomasound.com> e-mail: info@oklahomasound.com